

# EQUIPO SPLIT PISO / CIELO



## CEILING FLOOR TYPE

Model name	Ceiling Floor Indoor		TSP-018MDS	TSP-024MDS	TSP-036MDS	TSP-048MDS	TSP-060MDS
			R410a	R410a	R410a	R410a	R410a
Power supply		V/Ph/Hz	220-240V~/50Hz/1P	220-240V~/50Hz/1P	380-415V~/50Hz/3P	380-415V~/50Hz/3P	380-415V~/50Hz/3P
Cooling	Capacity	Btu/h	18000	24000	36000	48000	60000
	Capacity	W	5300	7200	10550	14000	16119
	Input	W	1712	2230	3578	4551	5594
	Rated current	A	7,78	10,1	7,8	9,30	12,00
	EER	W/W	3,10	3,23	2,95	3,08	2,88
Heating	Capacity	Btu/h	20000	26500	40000	53000	62500
	Capacity	W	5900	7900	12000	16000	17731
	Input	W	1782	2254	3468	4432	5147
	Rated current	A	8,50	11,2	7,2	9,50	12,40
	COP	W/W	3,29	3,35	3,46	3,61	3,44
Indoor air flow (Hi/Me/Lo)		m <sup>3</sup> /h	900/800/700	1200/1050/900	1700/1300/1100	2177/1689/1434	2177/1689/1434
Indoor noise level (Hi/Me/Lo)		dB(A)	43/41/38	45/43/40	45/43/40	52/49/46	52/49/46
Indoor dimension	Unit (WxHxD)	mm	1055x675x235	1055x675x235	1275x675x235	1635x675x235	1635x675x235
	Packing (WxHxD)	mm	1131x753x313	1131x753x313	1351x753x313	1711x753x313	1711x753x313
Indoor weight	Net	kg	23	24	29	38	38
	Gross	kg	29	30	35	46	46
Refrigerant	Type		R410A	R410A	R410A	R410A	R410A
Refrigerant pipe	Liquid side	mm	φ6.35	9,52	9,52	9,52	9,52
	Gas side	mm	φ12.7	φ15.88	φ19.05	φ19.05	φ19.05
Operation temperature range		°C	16 ~ 30	16 ~ 30	16 ~ 30	16 ~ 30	16 ~ 30

Outdoor air flow		m <sup>3</sup> /h	2400/1850	4000/2450	4900/2750	6300/4650	6300/4650
Outdoor noise level		dB(A)	49/55	54/58	55/58	57/60	57/60
Outdoor dimension	Unit (WxHxD)	mm	780x605x290	900x650x310	900x805x360	1250x940x340	1250x940x340
	Packing (WxHxD)	mm	883x412x653	1015x720x425	1031x925x447	1365x1030x430	1365x1030x430
Outdoor weight	Net	kg	42	54	79	103	108
	Gross	kg	47	59	87	113	118